



THE NEW ART OF GRINDING - SURFACE GRINDING MACHINES Z-SERIES



SURFACE GRINDING MACHINES Z-SERIES

Features

- Sturdy, cast iron execution of all machine components
- High machine weight for maximum rigidity
- Preloaded precision linear guideways in the vertical- and cross axis (Bosch Rexroth) for highest accuracy
- Scraped and turcite coated slideways in the longitudinal axis provide excellent vibration absorption and a high-quality grinding surface pattern.
- Hydraulic longitudinal motion with return cooling unit to achieve good surfaces
- Electro-mechanic cross- and vertical motion
- Measuring systems in vertical axis (Heidenhain) for precise positioning
- Maintenance-free paper band filtration unit with up to 500l tank and 2-bar pressure pump for effective cooling and rinsing

- Integrated rinsing channel
- Magnetic separator for prefiltration of the paper band filtration unit
- Infinitely variable grinding spindle motor
- Machine lamp
- Table-mounted dressing device for high precision and surface finish
- Electro-permanent magnetic chuck (SAV) with integrated pole changing unit and traction regulation
- Partial encapsulation of the machine with sliding door and a service door
- Effective splash guard and an excellent accessibility
- Preparation of the machine for installation of a coolant mist exhaust unit

Control system features

- Very comfortable and easy to operate Z-control
- Automatic vertical infeed with dressing amount compensation
- Fully automatic grinding cycle with dressing cycles
- Easy operation via touchscreen
- Large and clear colour screen (10.4")
- Electronic handwheel, usable in vertical- and cross axis

Machine type		Z 24	Z 48	Z 510	Z 612	Z 715
Grinding range	mm	400 x 250	800 x 500	1,000 x 600	1,200 x 700	1,500 x 800
Cross travel	mm	220	450	550	650	750
Longitudinal travel	mm	600	1,200	1,400	1,600	1,900
Distance table to spindle centre	mm	540	600	600	600	600
Size of magnetic chuck	mm	400 x 200	800 x 400	1,000 x 500	1,200 x 600	1,500 x 700
Table load incl. magnetic chuck	kg	250	700	1,000	1,300	1,600
Infeed longitudinal axis	mm/min	1,000 - 30,000	1,000 - 30,000	1,000 - 30,000	1,000 - 30,000	1,000 - 30,000
Infeed cross axis	mm/min	0.01 - 2,000	0.01 - 2,000	0.01 - 2,000	0.01 - 2,000	0.01 - 2,000
Infeed vertical axis	mm/min	0.001 - 1,500	0.001 - 1,500	0.001 - 1,500	0.001 - 1,500	0.001 - 1,500
Grinding wheel dimensions	mm	250 x 38 x 50.8	400 x 50 x 127	400 x 80 x 127	400 x 80 x 127	400 x 80 x 127
Grinding spindle drive	kW	3.7	11	11	11	11
Control range grinding spindle motor	U/min	1,000 - 4,500	1,000 - 3,000	1,000 - 3,000	1,000 - 3,000	1,000 - 3,000
Machine dimension [L x W x H(max)]	mm	3,050 x 2,050 x 2,300	4,350 x 2,420 x 2,380	4,800 x 2,400 x 2,500	5,160 x 2,720 x 2,380	5,750 x 2,850 x 2,650
Machine weight (approx.)	kg	2,900	6,660	7,500	8,340	9,300



SCHLEIFMASCHINEN

Ziersch GmbH
Am Vogelherd 60
98693 Ilmenau, Germany

☎ +49 3677 76132-0

www.ziersch.com
info@ziersch.com

FERTIGUNGSTECHNIK

Ziersch Fertigungstechnik GmbH & Co. KG
Am Vogelherd 26
98693 Ilmenau, Germany

☎ +49 3677 6402-0

www.ziersch.com
info@ziersch-fertigungstechnik.com